

# FIBER OPTIC GYROSCOPE

## VG103S-2LN



### PHYSICAL PARAMETERS

Dimensions	mm	Ø55 x 17	ISO 2768-m
Weight	gram	40	
Housing		plastic	IP67

\* With magnetic shield

### PERFORMANCE

Input range	°/s	100	for info
Bias, RMS	°/h	1	Allan variance min
ARW	°/√h	0.006	white noise PSD
Bandwidth	kHz	1	2nd order LPF
SF, RMS	%	0.02	day-to-day
Magnetic response	°/h/Gauss	1 (0.03*)	typical

### ELECTRICAL INTERFACE

Start-up	s	0.03	
Powering	W	0.5	+5V

### ENVIRONMENT

Operating temperature	°C	-40...+70	
Endurance temperature	°C	-55...+85	> 2 h, non-operating
Vibration, RMS	g	18	20 Hz... 2000 Hz
Shocks	g	750	1 ms half-sine

### RELIABILITY

MTBF / Lifetime	yr	15	humidity conditions applied
-----------------	----	----	-----------------------------

fizoptika.com

Datasheet

Feb 2021

*Fizoptika reserves the right to change the design or specifications at any time without prior notice. All pictures shown are for illustration purpose only. The actual product may vary due to the ongoing product enhancement.*