



# FIBER OPTIC GYROSCOPE

## VG191A



### PHYSICAL PARAMETERS

Dimensions	mm	Ø24 x 40	ISO 2768-m
Weight	gram	30 (40*)	
Housing		Al alloy ( $\mu$ -metal*)	IP67

\* Shielded VG191A

### PERFORMANCE

Input range	°/s	250	for info
Bias, RMS	°/h	1	Allan variance min
ARW	°/√h	0.015	white noise PSD
Bandwidth	kHz	1	
SF, RMS	%	0.02	day-to-day
Magnetic response	°/h/Gauss	4 (0.1*)	typical

### ELECTRICAL INTERFACE

Start-up	s	0.03	
Powering	W	0.5	+5V

### ENVIRONMENT

Operating temperature	°C	-40...+70	
Endurance temperature	°C	-55...+85	> 2 h, non-operating
Vibration, RMS	g	18	20 Hz... 2000 Hz
Shocks	g	750	1 ms half-sine

### RELIABILITY

MTBF / Lifetime	yr	15	humidity conditions applied
-----------------	----	----	-----------------------------

fizoptika.com

Datasheet

Jun 2020

Fizoptika reserves the right to change the design or specifications at any time without prior notice. All pictures shown are for illustration purpose only. The actual product may vary due to the ongoing product enhancement.